


Our standard range

lisocore® with wood fibre cover layer		Thickness mm	Density kg/m ³	
lisocore® with HDF raw cover layer Size: 2.800 x 2.070 mm		16,0	470	
		19,0	400	
		25,0	315	
lisocore® with MDF raw cover layer Size: 2.800 x 2.070 mm		38,0	320	
		50,0	240	
		60,0	200	
NEW! Our melamine selection		Thickness mm	Density kg/m ³	
lisocore® RECOAT with melamine-faced cover layer Size: 2.800 x 2.070 mm		16,0	500	
		19,0	420	
		25,0	345	
		38,0	330	
		50,0	255	
		60,0	215	
lisocore® RECOAT is ideal for the material-saving application of primer or lacquer!				
All colours of our melamine selection:				
 Brilliant White K8681 / SU	 Basic White K0101 / SM	 Grey K0112 / ST	 Anthracite K0162 / ST	 Nature Oak K3025 / MV

... if a little less weight is requested

lisocore® ultra-light	Thickness mm	Density kg/m ³
<p>lisocore® with plywood cover layers raw</p> <p>Appearance class I/I</p> <p>Size: 2.440 x 1.220 mm</p> <p>For extra light applications and optimal finish foil coating results</p>	 <p>15,0</p>	<p>270</p>

... in practical application

lisocore® as sliding-door panel	Thickness mm	Density kg / Panel
<p>lisocore® with melamine-faced cover layer</p> <p>lisocore® RECOAT</p> <p>Size: 2.800 x 2.070 mm</p> <p>with Birch-Multiplex-Inlays (2070 x 95 mm) on both sides for all highly demanding fastening systems</p>	 <p>Basic White K0101 / SM</p> <p>40,0</p>	<p>80</p>

For all items from our standard range is valid:



MOQ: 1 pallet
Delivery time: 2 - 3 weeks

... or contact your distributor!