lisocore®

Standard range

lisocore® CLASSIC

	Thickness mm	Density kg/m³
lisocore® with **HDF raw** cover layer Size: 2.800 x 2.070 mm 3.050 x 1.300 mm	15,0	395
	19,0	330
	25,0	315
lisocore® with **MDF raw** cover layer Size: 2.800 x 2.070 mm 3.050 x 1.300 mm	38,0	320
	50,0	240
	60,0	200

lisocore® ULTRA LIGHT

	Thickness mm	Density kg/m³
lisocore® with **plywood cover layers raw** Appearance class I/I Size: 2.440 x 1.220 mm For extra light applications and optimal finish foil coating results	15,0	300

lisocore® SLIDE

	Thickness mm	Density kg/Panel
lisocore® with **melamine-faced cover layer** lisocore® RECOAT Size: 2.800 x 2.070 mm with laminated veneer lumber inlays firmly glued at the top, removable at the bottom for all highly demanding fastening systems	40,0	80

Front White
0101 SM

lisocore® RECOAT

with
melamine-faced cover layer
Front White 0101 SM
Size: 2.800 x 2.070 mm

lisocore® RECOAT is ideal for the material-saving application of primer or lacquer!

Thickness mm	Density kg/m³
16,0	510
19,0	430
25,0	345
38,0	330
50,0	255
60,0	215

From 38,0 mm thickness also available in following decors:

Brilliant White
8681 SU

Stone Grey
0112 PE

Graphite Grey
0162 PE/ST

Anthracite
0164 PE

Gold Craft
Oak
K003 PW

Honey Castello Oak
K358 PW

Amber Urban
Oak
K006 PW

Sand Barbera
Oak
K543 SN

Gold Baroque
Oak
K535 RW

Tobacco Franklin
Walnut
K547 RW

lisocore® FR

flame retardant
B-s2, d0 according to EN 13501-1

Size: 2.850 x 2.100 mm
MOQ: 400 boards

Thickness mm	Density kg/m³
38,0	470

For all items from our standard range is valid:

MOQ: 1 pallet
(lisocore®FR 400 boards)

Pyrus Panels | Icom Advanced Materials GmbH
Betriebsstätte Bad Aibling
Carl-von-Ossietzky-Str. 17-21
83043 Bad Aibling

Handelsregister AG Eschwege HRB 3711
Steuernummer 026/236/00342
Umsatzsteuer ID Nr. DE451430360
Geschäftsführer: Ales Kopal

Bankverbindung:
Commerzbank AG
IBAN: DE04 5224 0006 0171 0516 00
BIC: COBADEFFXXX